To mitigate the possibility of overheating of equipment, control energy costs, and guard against possible downtime in today's busy data centers, Panduit has provided solutions for reducing bypass airflow through open spaces in racks and cabinets. From the basic Rack Filler Panels and the truly Tool-less Blanking Panels, to the revolutionary 4 RU – 51 RU, easy-to-install/operate Full-Length Blanking Shade, Panduit offers a full array of blanking solutions.







**Rack Filler Panels** 

**Full-Length Blanking Shade** 

**Tool-less Blanking Panels** 

	Hadik i illoi i alloid	ran Longar Diamang Onaco	1001 1000 Diamang Landio
Part Number	DPFP1*, DPFP2*, DPFP4*, DPFP8*, CPAF1BLY, CPAF1WH, CPAF2BLY, CPAF2WH, CPATC^	FLBSIM-51	TLBP1S-V**, TLBP2S-V**, TLBP1R-V**, TLBP2R-V**
Installation	Positive engagement with screws (provided) to secure filler panels tomounting rails	No tools/additional hardware required; optional clip to improve sealing capabilities	No tools/hardware required
Installation Time	Slow; requires minimum of two screws per panel	Extremely fast for full cabinet deployment	Fast; simply snap panels in place
Available Configurations	1 RU, 2 RU, 4 RU, 8 RU	4 RU – 51 RU; adjusts for square-punched or round-tapped holes in mounting rail	1 RU, 2 RU; both round-hole or square-hole options (with or without cage nuts installed)
Sealing Capabilities	GOOD	BETTER	BEST
Special Features	Reserve rack space for future use; direct airflow in cabinet applications; angled versions available for compatibility with angled patch panels	Most suitable for a large number of consecutive rack units; easily adjusts as adjacent equipment is installed or removed	Minimize bypass airflow in standard EIA 19" racks and cabinets while providing an aesthetic appearance; passthrough panel on TLBPBPT1S allows cable to pass from front to back of cabinets while still maintaining sealing capabilities
Packaging	Single-piece packaging	Single-piece packaging	Five-piece packaging for TLBP1S-V**, TLBP2S-V**, TLBP1R-V**, and TLBP2R-V**

<sup>\*</sup>Colors other than black: WH (White)
^Colors: BL (Black) and WH (White)

To seal inconsistently sized openings that do not conform to above blanking solutions, Panduit offers Blanking Foam Strips to minimize gaps in and around network cabinets to prevent bypass air. Removable and repositionable, the adhesive-backed foam strips can be stacked, folded, rolled, or manipulated to seal various-size openings not typically filled by tool-less blanking panels or other standard blanking options. Single-roll packaging — 4.00 in. x 100.0 in. (101.6mm x 2540.0mm).

<sup>\*\*</sup>Colors other than black: add 10 to indicate white