


FEMALE TO MALE  
PAN MPO PATCHCORD SHOWN

NOTES:

1. SEE SHEETS 2,3,& 4 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS.
2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY.
3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON.
4. TESTED TO EIA/TIA 568-C.3.
5. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2011/65/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

						TITLE FIBER OPTIC PATCH CORD PAN MPO TO PAN MPO CUSTOMER DRAWING						
						ITEM REVISION NAME 10F093BF/00		<b>PANDUIT</b>				
						DATASET FILE NAME 10F093BF_DC/00A						
						UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)						
						.x ± .03 (0.8)      .xxx ± .010 (0.3) .xx ± .03 (0.8)      ANGLES ±						
R	05-21-13	MC	JDK	SFDO	RELEASED TO PRODUCTION	10F093BF-DC		MATERIAL: SEE NOTES				
						DRAWING NUMBER: 10F093BF-DC						
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY MC	DATE 05-14-13	CHK JDK	SCALE NONE	DRAWING NUMBER: SHT 1 OF 4	SIZE A



THIRD ANGLE  
PROJECTION

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



FEMALE TO FEMALE - PAN MPO TO PAN MPO FIBER OPTIC PATCH CORD								
PANDUIT PART NO.	CABLE				MTP CONNECTOR			
	RATING	FIBER TYPE	COUNT	COLOR	PERFORMANCE	POLARITY	BOOT COLOR	
F5TRP7N7NANM***	PLENUM (OFNP)	OM2	12	ORANGE	STANDARD	METHOD A	BLACK	
FXTRP7N7NANM***		OM3		AQUA	STANDARD			
FXTRP7N7NXNM***					OPTIMIZED			
FXTRP7N7NBNM***					STANDARD			
FXTRP7N7NYNM***					OPTIMIZED			
FZTRP7N7NANM***			OM4		AQUA	STANDARD		METHOD A
FZTRP7N7NXNM***		OPTIMIZED						
FZTRP7N7NBNM***		STANDARD		METHOD B				
FZTRP7N7NYNM***		OPTIMIZED						
F5TRL7N7NANM***		LOW SMOKE ZERO HALOGEN (LSZH)		OM2		12		
FXTRL7N7NANM***	OM3		AQUA	STANDARD				
FXTRL7N7NXNM***				OPTIMIZED				
FXTRL7N7NBNM***				STANDARD	METHOD B			
FXTRL7N7NYNM***				OPTIMIZED				
FZTRL7N7NANM***				OM4	AQUA	STANDARD	METHOD A	
FZTRL7N7NXNM***	OPTIMIZED							
FZTRL7N7NBNM***	STANDARD		METHOD B					
FZTRL7N7NYNM***	OPTIMIZED							

\*\*\* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

						TITLE FIBER OPTIC PATCH CORD PAN MPO TO PAN MPO CUSTOMER DRAWING						
						ITEM REVISION NAME 10F093BF/00						
						DATASET FILE NAME 10F093BF_DC/00A						
						UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm) .X ± .xxx ± .010 (0.3) .XX ± .03 (0.8)      ANGLES ±						
						MATERIAL: SEE NOTES SHEET 1						
						DRAWING NUMBER: 10F093BF-DC						
R	05-21-13	MC	JDK	SFDO	RELEASED TO PRODUCTION	10F093BF-DC						
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY	DATE	CHK	SCALE	DRAWING NUMBER	SIZE
							MC	05-15-13	JDK	NONE	SHT 2 OF 4	A

MALE TO MALE - PAN MPO TO PAN MPO FIBER OPTIC PATCH CORD								
PANDUIT PART NO.	CABLE				MTP CONNECTOR			
	RATING	FIBER TYPE	COUNT	COLOR	PERFORMANCE	POLARITY	BOOT COLOR	
F5TRP8N8NANM***	PLENUM (OFNP)	OM2	12	ORANGE	STANDARD	METHOD A	BLACK	
FXTRP8N8NANM***		OM3		AQUA	STANDARD			METHOD B
FXTRP8N8NXNM***					OPTIMIZED			
FXTRP8N8NBNM***					STANDARD	METHOD A		
FXTRP8N8NYNM***					OPTIMIZED			
FZTRP8N8NANM***		OM4		AQUA	STANDARD	METHOD A		
FZTRP8N8NXNM***			OPTIMIZED					
FZTRP8N8NBNM***			STANDARD		METHOD B			
FZTRP8N8NYNM***			OPTIMIZED					
F5TRL8N8NANM***		LOW SMOKE ZERO HALOGEN (LSZH)	OM2	12	ORANGE	STANDARD	METHOD A	BLACK
FXTRL8N8NANM***	OM3		AQUA		STANDARD	METHOD B		
FXTRL8N8NXNM***					OPTIMIZED			
FXTRL8N8NBNM***					STANDARD	METHOD A		
FXTRL8N8NYNM***					OPTIMIZED			
FZTRL8N8NANM***	OM3		AQUA		STANDARD	METHOD A		
FZTRL8N8NXNM***				OPTIMIZED				
FZTRL8N8NBNM***				STANDARD	METHOD B			
FZTRL8N8NYNM***				OPTIMIZED				

\*\*\* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

							TITLE FIBER OPTIC PATCH CORD PAN MPO TO PAN MPO CUSTOMER DRAWING						
							ITEM REVISION NAME 10F093BF/00						
							DATASET FILE NAME 10F093BF_DC/00A						
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)					MATERIAL: SEE NOTES SHEET 1	
							.x ± .xxx ± .010 (.3) .xx ± .03 (.08)      ANGLES ±					DRAWING NUMBER: 10F093BF - DC	
R	05-21-13	MC	JDK	SFD0	RELEASED TO PRODUCTION	10F093BF - DC			THIRD ANGLE PROJECTION				
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY	DATE	CHK	SCALE	DRAWING NUMBER:		
							MC	05-15-13	JDK	NONE	SHT 3 OF 4		
											SIZE A		

2

1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FEMALE TO MALE - PAN MPO TO PAN MPO FIBER OPTIC PATCH CORD


PANDUIT PART NO.	CABLE				MTP CONNECTOR				
	RATING	FIBER TYPE	COUNT	COLOR	PERFORMANCE	POLARITY	BOOT COLOR		
F5TRP7N8NANM***	PLENUM (OFNP)	OM2	12	ORANGE	STANDARD	METHOD A	BLACK		
FXTRP7N8NANM***		OM3		AQUA	STANDARD			OPTIMIZED	
FXTRP7N8NXNM***					STANDARD	OPTIMIZED			
FXTRP7N8NBNM***					STANDARD	OPTIMIZED			
FXTRP7N8NYNM***					STANDARD	OPTIMIZED			
FZTRP7N8NANM***		OM4		AQUA	STANDARD	METHOD A		METHOD B	BLACK
FZTRP7N8NXNM***					OPTIMIZED	METHOD A			
FZTRP7N8NBNM***					STANDARD	METHOD B			
FZTRP7N8NYNM***					OPTIMIZED	METHOD B			
F5TRL7N8NANM***		LOW SMOKE ZERO HALOGEN (LSZH)		OM2	12	ORANGE		STANDARD	METHOD A
FXTRL7N8NANM***	OM3		AQUA	STANDARD		OPTIMIZED			
FXTRL7N8NXNM***				STANDARD		OPTIMIZED			
FXTRL7N8NBNM***				STANDARD		OPTIMIZED			
FXTRL7N8NYNM***				STANDARD		OPTIMIZED			
FZTRL7N8NANM***	OM3		AQUA	STANDARD		METHOD A	METHOD B	BLACK	
FZTRL7N8NXNM***				OPTIMIZED		METHOD A			
FZTRL7N8NBNM***				STANDARD		METHOD B			
FZTRL7N8NYNM***				OPTIMIZED		METHOD B			

\*\*\* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

B B

B B

A A

TITLE FIBER OPTIC PATCH CORD PAN MPO TO PAN MPO CUSTOMER DRAWING		
ITEM REVISION NAME 10F093BF/00	<b>PANDUIT™</b>	
DATASET FILE NAME 10F093BF_DC/00A		
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm) .x ± .1 (2.54) .xxx ± .005 (.127) .xx ± .01 (.25) ANGLES ± 5°		MATERIAL: SEE NOTES SHEET 1
DRAWING NUMBER: 10F093BF-DC		
THIRD ANGLE PROJECTION 		

R	05-21-13	MC	JDK	SPDO	RELEASED TO PRODUCTION	10F093BF-DC
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
MC	05-15-13	JDK				

DRAWN BY	DATE	CHK	SCALE	SIZE
MC	05-15-13	JDK	NONE	A



2

1