



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

TABLE 1: MPO FERRULE POSITION (END A TO END B)

Table with columns for Fiber Color, End A (Method A), and End B (Method A and Method B). Rows list fiber colors from BLUE to AQUA with corresponding MPO positions.

TABLE 2: 24-FIBER INTERCONNECT PART NUMBER MATRIX

Matrix table with columns 1-15 and rows F, U, R, N. Includes technical specifications: LENGTH (001 TO 030 M), UNIT OF MEASURE (F, M), PULLING EYE (N), PERFORMANCE/POLARITY (A, X, Y), CONNECTOR VARIANTS (E, J), FLAME RATING (P, L), CABLE TYPE (R), FIBER COUNT (U), FIBER TYPE (X, Z, 9), and PRODUCT DESIGNATION (F).

B

B

←

→

A

A

Revision table with columns: REV, DATE, BY, CHK, APR, DESCRIPTION, ECN, TITLE, ITEM REVISION NAME, DATASET FILE NAME, MATERIAL, DRAWING NUMBER, and SIZE. Includes drawing title '24 FIBER MPO (MP024) INTERCONNECT CABLE ASSEMBLIES' and drawing number '00078EFL-DC'.