

IndustrialNet™ Category 5e SF/UTP Copper Cable

specifications

Category 5e 2-pair SF/UTP copper cable shall meet or exceed the IEC 61156-6, ANSI/TIA-568-C.2 Category 5e and ODVA EtherNet/IP standards up to 80 meters. The stranded copper conductors shall be 24/7 AWG with foamed polyethylene (PE) insulation. The copper conductors shall be twisted in pairs. Both pairs shall then be surrounded by an overall metallic foil and braided shield and covered with a polyurethane (PUR) jacket. The jacket shall be oil, ozone, and abrasion resistant for enhanced chemical resistance and mechanical performance. The jacket shall be flame retardant and halogen-free for industrial Ethernet applications. The cable shall support high flex and torsion applications.



technical information

Electrical performance:	Certified component performance up to 80 meters and exceeds the requirements IEC 61156-6 and ANSI/TIA-568-C.2 Category 5e and ODVA EtherNet/IP standards at swept frequencies up to 100 MHz
Standard compliances:	Flexure IEC 61935-2 Flex Life Test: 1 million cycles at 10x cable diameter; 10 million cycles at 20x cable diameter Torsion Life Test: 3 million cycles, 360° Ozone resistance VDE 0472-805 Oil resistance EN 60811-2-1 (7 days x 24hrs/90°C)
Conductors/insulators:	Two pairs of 24/7 AWG stranded copper insulated with foamed polyethylene
Insulation diameter:	1.15 – 1.25mm (0.045 – 0.049 in.)
Flame rating:	Flame retardant, halogen-free – IEC 60332-1-2, IEC 60754-1; EN50575: Euroclass Eca
Installation tension:	80 N (18 lbf) maximum
Temperature rating:	-40°C to 80°C (-40°F to 167°F) during transport, installation, and operation
Cable jacket:	Polyurethane (PUR), oil, ozone, and abrasion resistant
Cable diameter:	6.4mm (0.252 in.) nominal
Cable weight:	22.5 kg/500m (50 lbs./1640 ft.)
Packaging:	Packaged 500 meters (1640 feet) on a reel Package tested to ISTA Procedure 1A

key features and benefits

Third party tested	Cable has been tested by an independent laboratory and complies with the electrical standard requirements of IEC 61156-6 Category 5e and ANSI/TIA-568-C.2 Category 5e standards
Reliability	Shielded SF/UTP cable construction protects against environmental elements that can cause electrical performance failures; stranded conductors for standard flex applications and ease of installation; cable jacket shall be oil, ozone, and abrasion resistant for enhanced chemical resistance and mechanical performance
Ethernet/IP Compliant	Enhanced design to provide performance levels required to support industrial network applications; meets ODVA Ethernet/IP performance requirements
Descending length cable markings	Easy identification of remaining cable reduces installation time and cable scrap
Packaged on a reel	Ensures proper performance and provides quick installation

applications

IndustrialNet™ Category 5e SF/UTP Copper Cable provides reliability and high performance as an integral component of the end-to-end solution for industrial Ethernet and Ethernet/IP based communications networks. The 2-pair high performance cable ensures highest availability in conditions seen in industrial environments. The cable incorporates a durable PUR jacket for use in installations requiring cable with a halogen-free rating.

Key applications include:

- 10BASE-T (Ethernet)
- 100BASE-T (Fast Ethernet)
- Industrial Ethernet
- Ethernet/IP
- Downlinks from control panel to the machine area
- Industrial deployments requiring protection against moisture ingress

IndustrialNet™ Category 5e SF/UTP Copper Cable

Flame retardant, halogen-free
2-pair: ISFX5502A*-LED

IndustrialNet™ Category 6/5e RJ45 Field Terminable Plug

Field terminable plug: ISPS688FA

IndustrialNet™ M12 D-Code Field Terminable Plug

Field terminable plug: ISPS5E44MFA

IndustrialNet™ Category 5e Shielded 600 V-Rated Patch Cords

CM/CMX: **ISTPHCH1MTL

IndustrialNet™ M12 D-Code to RJ45 Panel Mount Adapter

Panel mount adapter: ICAM12DRJS

Mini-Com® Modular Patch Panel

8-port: CDPP8RG

DIN Rail Adapter

1-port: CADIN1IW***

*To designate color, add suffix TL (Teal) or RD (Red).

**For other lengths, change the length designation (1M) of the part number to the desired length (0.3M, 0.6M, 2M, 3M, 5M, or 10M); to designate color, replace TL (Teal) suffix with BL (Black), RD (Red), or YL (Yellow). For example, the part number for a 2-meter teal patch cord is ISTPHCH2MTL.


***For standard colors other than Off White, replace IW in part number with BL (Black), EI (Electric Ivory), IG (International Gray), or WH (White).

IndustrialNet™ Category 5e SF/UTP Copper Cable

additional specifications

Mechanical Test	
Ultimate Breaking Strength	>400 N (90 lbf.)
Minimum Bend Radius	8x cable diameter
Electrical Test	
Nominal Velocity of Propagation (NVP)	72%
Operating Voltage, Maximum	80V

cable construction



Dimensions are in inches. [Dimensions in brackets are metric].

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

iai@panduit.com

PANDUIT®

©2018 Panduit Corp.
ALL RIGHTS RESERVED.
COSP343--WW-ENG
4/2018