	2							1						
	THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.							JIT CORP.						
B	OPTICAL SUB-UNIT FIBER STRENGTH MEMBERS COO OCO OCO OCO OCO OCO OCO OCO OCO OC							 NOTES: 1. DIAMETER DIMENSION, SHOWN FOR REFERENCE ONLY. 2. DIMENSIONS IN BRACKETS [] ARE ENGLISH. 3. FOR PART NUMBERS AND LENGTHS OTHER THAN THOSE SHOWN, CONTACT YOUR PANDUIT SALES PERSON. 4. ALL MATERIALS AND COMPONENTS USED MUST MEET THE MATERIAL RESTRICTIONS OF RoHS (EUROPEAN DIRECTIVE 2011/65/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE ROHS TECHNICAL ADAPTATION COMMITEE. 						
		[.72]			(†				Т	ECHNICAL				
				/				МАХ	IMUM LOSS - MU	JLTIMODE	INSTALLA		LONG TERM	_
									3.5 dB/KM @ 8 1.5 dB/KM @ 13		36.6c	m	18.3cm [7.2"]	-
1							_	MAX	IMUM LOSS - SI	NGLEMODE	Т	ENSIL	E LOAD	=
									.75 dB/KM @ 13	310nm	INSTALLA	TION	LONG TERM	
		_				CENTRAL STRENGTH MEMBER			.75 dB/KM @ 15	550nm	1320 [300 6		396 N [89 6f]	
					JTER – .CKET					TEMPER	RATURE			-
								-	NSTALLATION	OPER/			STORAGE	
									0°C TO +60°C 'F TO +140°F		0 +70°C +158°F		°C TO +70°C °F TO +158°F	
									TITLE					
A													OR CABL	Ε
									VV I I H	1 900u	m llGt omer draw		UFFEK	
									ITEM REVISION NAME					
									DATASET FILE NAME MO2055	KF_DC/00A	\		ANDUI	
									UNLESS OTHER DIMENSIONAL TOLE .X ± .XX ± .03 [0.8]	RWISE SPECIF ERANCES ARE:	IED, IN [mm] 10 [0.3]		EE TABLE	
	00	02-17-14	SAT	WMA	тсв	RELEASED TO PRODUCTION	M02055KF	-DC		TH I RD PROJE	ANGLE	rawing nume)2055KF - DC	
	REV	DATE	BY	СНК	APR		ECN		DRAWN BY DATE SAT 02-17-14	CHK SCAL WMA	e NONE	SH	T 1 OF 2	size A

2

1

В

 \rightarrow

A

2

В

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT Part no.	FIBER TYPE	JACKET FLAME RATING			
FLKR548	MULTIMODE	OFNR			
FLKL548	50/125 OM2	LSZH			
FLKR648	MULTIMODE	OFNR			
FLKL648	62.5/125 OM1	LSZH			
FLKRX48	MULTIMODE	OFNR			
FLKLX48	50/125 OM3	LSZH			
FLKRZ48	MULTIMODE	OFNR			
FLKLZ48	50/125 OM4	LSZH			
FLKR948	SINGLEMODE	OFNR			
FLKL948	9/125	LSZH			

В

Α

							-			
A								48 FIBER INDOOR/OUTDOOR CABLE WITH 900um TIGHT BUFFER		
								CUSTOMER DRAWING		
								DATASET FILE NAME MO2055KF/00		
								UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]		
								x ± .xxx ± .010 [0.3] SEE TABLE .xx ± .03 [0.8] angles ±		
	00	02-17-14	SAT	WMA	тсв	RELEASED TO PRODUCTION	M02055KF-DC	C THIRD ANGLE PROJECTION MO2055KF-DC		
	REV	DATE	BY	СНК	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE SIZE SAT 02-17-14 WMA NONE SHT 2 OF 2 A		
2						2		1		