	2						1						
	THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN AN								WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.				
						◄─── 1.61 ── → [40.9]			PANDUIT P/N		WEIGHT		
									JASSP6TGIW	.2	28 LB/10 PCS 27 g/10 PCS)		
в						VIEW SHOWN WITH A R ANGLE TERMINATION C		PAF COL 2. SEE PAF 3. DIN ME 4. PAF 1-	L E CURRENT CATA RT NUMBER SUFF _OR AND OR PAC E CATALOG FOR RTS APPLICABLE RT. MENSIONS IN PA TRIC. RT INCLUDES: ADAPTER WITH	LOG F IXES KAGE COMPL FOR RENTH	TOR ADDITIONAL TO INDICATE QUANTITY. ETE LIST OF USE WITH THIS HESES ARE IN	в	
~	•		1.41	/CAT/		 1.64 [41.8] 1.21 [30.7] 	-	1 - 1 -	LAN/CAT6 PRIN MINI-COM CAT6 RIGHT ANGLE T	JACK ERMIN	MODULE NATION CAP		
5	LAN/CAT6 .88 [22.3] .88 [22.3] .1.73 [44.0] VIEW SHOWN WITH / STANDARD TERMINATION												
								MINI-COM		SPRING KIT	SHUTTERED ADAPT		
							CUSTOMER DRAWING						
								DATASET FILE NAME	M02079CA/00		PANDUI		
								N	102079CA_DC01/00A	M/			
								UNLESS DIMENSIONAL .× ± .1 [2 .×× ± .01 [.1271	ADAPTER- ABS DOOR- ABS SPRING- SPRING STEEL		
	9/06/16	MDJR	NAGL	MMR	RELEASED TO PRODUCTION		02079CA-01		THIRD ANG PROJECTIO	LE	RAWING NUMBER:		
F RE	V DATE BY CHK APR DESCRIPTION				ECN	MDJR 6/	29/16 MMR SCALE NO	NE	SHT 1 0F 1	A			
		·	•	·	2			· · · · ·	1	I			