


# Dual Display Conference Room

Meeting spaces provide a chance for people to collaborate, sharing divergent designs, plans, and viewpoints. Adding video conferencing capabilities allows teams to be spread over geographical distances. A single display is often no longer enough to accommodate the demands of presenting from multiple sources, or simultaneous display of shared content and remote participants. These days, AV technology must accommodate multiple inputs and outputs in a way that's cost-effective and easy to use.

## Needs Assessment

- Purpose** This dual display meeting space shall include an AV system that allows multiple users to share content from a variety of sources to either or both displays and supports popular video conferencing software
- Display** Two flat panel displays of sufficient size for critical viewing by all participants
- Sources** Wireless and wired BYOD devices, room PC, PTZ camera
- Control** System on / off, source selection, and audio controls should be intuitive for non-frequent users
- Audio** Microphone for capturing in-room presenters, plus amplifier and ceiling speakers for video conference and program audio playback
- Cable** Select the appropriate cabling solutions for source devices, network connections, and HDBaseT extension



## AV Routing

The Atlona **AT-OME-MS52W** 5x2 matrix switcher with USB and wireless link is the heart of the dual display AV system. Mounted at the conference table, it provides USB-C, HDMI<sup>®</sup>, and DisplayPort connections for BYOD devices and the room PC. It also supports native wireless AV casting so users can mirror content from their devices without an app. The OME-MS52W manages all audio sources and levels, providing the content to the amplifier through a stereo audio output.

The OME-MS52W also features both HDMI and HDBaseT video outputs which can display either the same or independent content. This matrix capability is crucial for viewing two sources simultaneously, such as when evaluating different ideas, or during video conferencing when presentation and participant gallery views are required.

In many conference spaces, running AV from a switcher to the display through floors, walls, and ceilings can involve cable runs of 50 feet or more. Therefore, this design takes advantage of the

HDBaseT output of the OME-MS52W which connects to an Atlona **AT-OME-EX-RX** receiver and supports extension of various signals up to 330 feet (100 meters) over a single shielded Category 6A cable. This includes video content from local or wireless sources and control signals for one display, as well as USB data for the PTZ camera. The HDMI output of the switcher is routed to an Atlona **AT-AVA-EX70-KIT** extender kit for transmission of video to the second display over HDBaseT.

## Wireless

The OME-MS52W interfaces with iOS<sup>®</sup>, Android<sup>™</sup>, Mac<sup>®</sup>, Chromebook<sup>™</sup>, and Windows<sup>®</sup> devices over Wi-Fi<sup>®</sup>, allowing screen mirroring without the need to install an app. Users can natively share material from their own devices with meeting attendees over the integrated access point, or the company's Wi-Fi network.

## PTZ Camera

The Atlona AT-HDVS-CAM delivers professional-grade video that is superior in image quality to a conventional webcam. Motorized pan, tilt, zoom, and preset support allows precise framing and recall for various meeting configurations.



# Dual Display Conference Room Bill of Materials

QTY	Description	SKU	
1	Atlona Omega 5x2 Matrix Switcher with USB and Wireless Link	AT-OME-MS52W	
1	Atlona Omega HDBaseT Receiver for HDMI with USB	AT-OME-EX-RX	
1	Atlona Avance™ 4K/UHD HDMI Extender Kit with Remote Power	AT-AVA-EX70-KIT	
1	Atlona PTZ Camera with USB	AT-HDVS-CAM	
1	Atlona Velocity System Hardware Gateway	AT-VGW-HW-3	
1	Atlona Velocity System 10" Touch Panel	AT-VTP-1000VL-BL	
1	Atlona Tabletop Mount for VTP-1000VL Touch Panels	AT-VTP-VTM	
1	Atlona IP to RS-232 Command Converter for Velocity System	AT-VCC-RS232-KIT	
1	Atlona Power Amplifier – 60 Watts	AT-GAIN-60	
1	Atlona Pocket™ Architectural Cable Access Enclosure	AT-PKT-3H	
1	Atlona LinkConnect USB-C to USB-C Cable	AT-LC-UC2UC-2M	
1	Panduit Small In-Wall Box	CMBBSWH	
1	Panduit Pan-Way Above Floor Raceway	Varies	
	<b>Category Cable Components:</b>	<b>Unshielded</b>	<b>Shielded</b>
	Panduit Category 6A Copper Cable	PUP6AV04BU-G	PUP6X04BU-UG
	Panduit Category 6A RJ45 Jack Module	CJ6X88TGBU	CJS6X88TGY
	Panduit Category 6A Field Term RJ45 Plug	FP6X88MTG	FPS6X88MTG
	Panduit Category 6A Patch Cord	UTP28X7BU	STP6X7BL
	Laptop, PC, display, projector, DSP, microphones, speakers, projection screen, and miscellaneous cabling	Furnished by others	



800-777-3300 | [cs@panduit.com](mailto:cs@panduit.com) | [panduit.com](http://panduit.com)



877-536-3976 | 408-962-0515 | [atlona.com](http://atlona.com)

© 2021 Panduit Corp. and Atlona Inc., a Panduit Company. All rights reserved. All brand names and trademarks or registered trademarks are the property of their respective owners.